


Metal Strip Current Sense Resistors Surface Mount

ULR Series

- Resistance R0005 (0.5mΩ) to R01 (10mΩ)
- Low TCR, Low inductance
- Designed for current sensing in power electronic systems
- Solid metal element withstands high current surges
- RoHS compliant



Electrical Data

		ULR1S	ULR1	ULR15S	ULR2	ULR25	ULR3
Footprint size		1206	2512	2010	2512	2512	2512
Power rating at 80°C	watts	1.0	1.0	1.5	2.0	2.5	3.0
Resistance range ¹	ohms	R001 to R01	R0005 to R01	R001 to R01	R0005 to R01	R0035 to R006	R0005 to R003
Isolation voltage	volts	200V	200V	200V	200V	200V	200V
TCR	ppm/°C	50	50, 75, 100, 150 See table below	50	50	50	50, 75, 100 See table below
Resistance tolerance	%	1(F), 5(J)					
Protective coating ²		None	Black	None	Black/Green	Green	Green
Standard values		See table below for available values					
Ambient temperature range	°C	-55 to +170					

Note 1: For values above 0R01 refer to our LR / LRF Series

Note 2: Colour of coating relates to solder process suitability, see Construction

Standard values available (non-standard values may be available to order - consult factory)

Value	ULR1S		ULR1		ULR15S		ULR2		ULR25		ULR3	
	Coat	TCR	Coat	TCR	Coat	TCR	Coat	TCR	Coat	TCR	Coat	TCR
R0005			Black	50			Black	50			Green	100
R00075			Black	50			Black	50			Green	100
R001	None	50	Black	50	None	50	Black	50			Green	50
R0015	None	50	Black	50	None	50	Black	50			Green	50
R002	None	50	Black	50	None	50	Black	50			Green	50
R0025	None	50	Black	150	None	50					Green	75
R003	None	50	Black	150	None	50					Green	75
R0035	None	50	Black	150	None	50			Green	50		
R004	None	50	Black	100	None	50			Green	50		
R0045	None	50	Black	100	None	50			Green	50		
R005	None	50	Black	100	None	50			Green	50		
R0055	None	50	Black	100	None	50			Green	50		
R006	None	50	Black	75	None	50			Green	50		
R007	None	50	Black	75	None	50	Green	50				
R008	None	50			None	50	Green	50				
R009	None	50			None	50	Green	50				
R01	None	50			None	50	Green	50				

General Note

Welwyn Components reserves the right to make changes in product specification without notice or liability. All information is subject to Welwyn's own test data and is considered accurate at time of print.

ÓWelwyn Components Limited

Welwyn Electronics Park, Bedlington, Northumberland, NE22 7AA, England. Tel: 01670 822181 Fax: 01670 829465 Web: www.welwyn-tt.com

March 2009

Construction

Black coat

A low TCR resistance alloy plate, with tin plated connection bands is protectively coated on the upper and lower faces and numerically marked with the resistance value. This part is suitable for wave or IR reflow soldering.

Green coat


A low TCR resistance alloy plate is grooved to set the final resistance, the lower faces are tin plated for connections, and it is protectively coated on the upper and lower faces and numerically marked with the resistance value. This part is ONLY suitable for IR reflow soldering.

Uncoated

A low TCR resistance alloy plate is grooved to set the final resistance and the lower face only is protected with an epoxy coating. The lower faces are tin plated for connections. This part is ONLY suitable for IR reflow soldering.

Marking

Only 2512 size parts are marked. For values which are integer numbers of milliohms, the marking is 4-character IEC62 code; e.g. "R002" for 2m Ω , "R010" for 10m Ω . For values including fractions of a milliohm the marking is 3 or 4-character code using "M" to indicate the decimal point, e.g. "M75" for 0.75m Ω , "1M50" for 1.5m Ω .




Termination Details:

Material Matt tin plated finish over a barrier layer
Solderability 95% min coverage (MIL-STD 202F / 208H, 235°C 2 secs)

Performance Data

		Maximum (+ 0.5m Ω)	
		Black & Uncoated	Green
Load at rated power (1000hrs cyclic load at 70°C)	$\Delta R\%$	± 1	± 1
De-rating from rated power at 80°C		See Graph	
Short term overload (5 x rated power for 5s)	$\Delta R\%$	± 0.5	± 1
Dry heat (96Hrs, no load, +155°C)	$\Delta R\%$	± 1	± 1
Temperature rapid change (-55 / +150°C, 100 cycles)	$\Delta R\%$	± 0.5	± 1
Resistance to solder heat (260°C for 10s)	$\Delta R\%$	± 0.5	± 1

Power de-rating graph



General Note

Welwyn Components reserves the right to make changes in product specification without notice or liability. All information is subject to Welwyn's own test data and is considered accurate at time of print.

Welwyn Components Limited


Welwyn Electronics Park, Bedlington, Northumberland, NE22 7AA, England. Tel: 01670 822181 Fax: 01670 829465 Web: www.welwyn-tt.com

March 2009

Recommended Solder Pad Layouts


2-wire pad layout.

Mounting Type	A	B	C
2512	4.75	1.8	3.6
2010	3.8	1.44	3.12
1206	2.375	0.9	1.95



4-wire pad layout.


Mounting Type	A	B	C	D
2512	4.75	1.8	1.45	1.0
2010	3.8	1.44	1.16	0.8
1206	2.375	0.9	0.725	0.5



Physical Data

Dimensions (mm) and weight (g)

Size	Coat	Values (mΩ)	L ±0.25	W	T ±0.20	D	Wt. (nom)	
2512	Green	0.5	6.35	3.18 ±0.35	0.60	2.68 ±0.25	0.09	
		0.75				2.48 ±0.25		
		1 – 1.5				1.43 ±0.25	0.08	
		2 – 3				1.18 ±0.25		
		4				2.18 ±0.25		
		5 – 6				1.93 ±0.25		
		7				1.43 ±0.25		
		8 – 10				1.18 ±0.25		
	Black	0.5		3.18 ±0.25	1.40	1.43 ±0.38	0.06	
		0.75						1.00
		1						0.80
		1.5						0.65
		2						0.50
		2.5						1.00
		3						0.70
		3.5						0.71
		4						0.60
		4.5						0.58
		5						0.50
		5.5						0.47
6	0.50							
7	0.45							
2010	None	1 – 10	5.08	2.54 ±0.15	0.60	1.67 ±0.63	0.04	
1206	None	1 - 10	3.20	1.6 ±0.10	0.60	0.98 ±0.38	0.02	



Flammability

The resistor will not burn or emit incandescent particles under any condition of applied temperature or overload.

Solvent resistance

The body protection and marking are resistant to all normal industrial solvents suitable for printed circuits.

Packaging

ULR parts are packed on a 2000 piece reel. Tape width is 8mm for 1206 and 12mm for 2010 and 2512.

General Note

Welwyn Components reserves the right to make changes in product specification without notice or liability. All information is subject to Welwyn's own test data and is considered accurate at time of print.

©Welwyn Components Limited


Welwyn Electronics Park, Bedlington, Northumberland, NE22 7AA, England. Tel: 01670 822181 Fax: 01670 829465 Web: www.welwyn-tt.com

March 2009

Ordering Procedure

Example: ULR2 at 2.5 milliohms and 1% tolerance on reel of 2000 pieces:

U L R 2 - R 0 0 2 5 F T 2



Tolerance (use IEC62 code)

F	1%
J	5%

Packing

T2	Tape	2512	2000 / reel	Standard
		2010		
		1206		

General Note

Welwyn Components reserves the right to make changes in product specification without notice or liability. All information is subject to Welwyn's own test data and is considered accurate at time of print.

Welwyn Components Limited

Welwyn Electronics Park, Bedlington, Northumberland, NE22 7AA, England. Tel: 01670 822181 Fax: 01670 829465 Web: www.welwyn-tt.com

March 2009